

General characteristics

Mechanical governor

Mechanically welded chassis with antivibration suspension

Power circuit breaker

Radiator for wiring T°of 50 °C max with mechanical fan

Protective grille for fan and rotating parts

9dB(A) silencer supplied separately

Charged DC starting battery with electrolyte

12 V charging alternator and starter

Supplied with oil and coolant -30°C

User manual and commissioning guide



[Documentation](#)

[Print](#)

415/240	17.6 / 22.0	16.0 / 20.0	30
400/230	17.6 / 22.0	16.0 / 20.0	31
380/220	17.6 / 22.0	16.0 / 20.0	33
240/120	17.6 / 22.0	16.0 / 20.0	52
230/115	17.6 / 22.0	16.0 / 20.0	55
220/110	17.6 / 22.0	16.0 / 20.0	57
220/127	16.0 / 20.0	14.5 / 18.2	52

Long : 1700 mm 720 Kg Net
Larg : 896 mm 830 Kg Brut
Haut :1221 mm



M127	74.9	65	Length : 2080mm Width : 960mm Height : 1415mm	950 Kg 1050 Kg	100 L
------	------	----	---	-------------------	-------

Switch boxes available :



Specifications :
Frequency meter, Ammeter, Voltmeter
Alarms and faultsOil pressure, water temperature, Overcrank, Overspeed (>60 kVA), Min/max alternator, Low fuel level, Emergency stop
Engine parameters :
Hours counter, Engine speed, Battery voltage, Fuel level, Alr preheating



Specifications :
Frequency meter, Ammeter, Voltmeter
Alarms and faults :
Oil pressure, water temperature, No start-up, Overspeed, Min/max alternator, Min/max battery voltage, Low fuel level, Emergency stop
Engine parameters :
Hours counter, Oil pressure, Water temperature, Engine speed, Battery voltage, Fuel level